

Monomanual I/A System reusable (Safe-Lock)

- Universal connector allows you to use your preferred cannulas with the same handpiece
- Tips manufactured with high-precision are designed to keep up with your changing intraoperative needs, from the capsulorhexis to cortical clean-up, to the most difficult 12 o'clock cortex removal
- Compatible with Phaco or I/A System via standard Luer connectors
- Swiss Design / Swiss Made

Universal handpiece



Art. No.	Description
SL 100	I/A Handpiece, monomanual (coaxial, Safe-Lock)

Exemplary pictures of I/A tip variants with metal sleeves



I/A Tip with metal sleeve, straight



I/A Tip with metal sleeve, angled



I/A Tip with metal sleeve, curved

I/A Tips with metal sleeve (no silicone sleeve needed)

Art. No.	Description
SL 110	I/A Tip, straight, 16G (Ø1.60mm), metal sleeve, asp. port Ø0.35mm, dual-side irrigation ports Ø0.98mm
SL 110/0.3	I/A Tip, straight, 16G (Ø1.60mm), metal sleeve, asp. port Ø0.30mm, dual-side irrigation. ports Ø0.98mm
SL 115	I/A Tip, straight, 16G (Ø1.60mm), metal sleeve, asp. port Ø0.50mm, dual-side irrigation. ports Ø0.98mm
SL 120 30°	I/A Tip, angled 30°, 16G (Ø1.60mm), metal sleeve, asp. port Ø0.30mm, dual-side irrig. ports Ø0.98mm
SL 120 45°	I/A Tip, angled 45°, 16G (Ø1.60mm), metal sleeve, asp. port Ø0.35mm, dual-side irrig. ports Ø0.98mm
SL 130	I/A Tip, angled 90°, 16G (Ø1.60mm), metal sleeve, asp. port Ø0.35mm, dual-side irrig. ports Ø0.98mm
SL 140	I/A Tip, curved, 16G (Ø1.60mm), metal sleeve, asp. port Ø0.35mm, dual-side irrigation ports Ø0.98mm

Exemplary pictures of I/A tip variants with silicone sleeves



I/A Tip with silicone sleeve, straight



I/A Tip with silicone sleeve, angled 30°



I/A Tip with silicone sleeve, angled 45°



I/A Tip with silicone sleeve, curved

Please note: The expected lifetime of our reusable medical devices is validated by a defined number of processing cycles. Please refer to the information provided in the instructions for use.

02/2026

Monomanual I/A System reusable (Safe-Lock)

I/A Tips straight for silicone sleeve irrigation (silicone sleeve needed, dual-side irrigation)

Art. No.	Description
SL 116	I/A Tip, straight, for silicone sleeve irrigation, 19G (Ø1.00mm), asp. port Ø0.35mm
SL 116 s4	I/A Tip, straight, for silicone sleeve irrigation, 19G (Ø1.00mm), asp. port Ø0.30mm
SL 117	I/A Tip, straight, for silicone sleeve irrigation, 20G (Ø0.90mm), asp. port Ø0.33mm
SL 116 s3	I/A Tip, straight, for silicone sleeve irrigation, 20G (Ø0.90mm), asp. port Ø0.30mm
SL 116 s2	I/A Tip, straight, for silicone sleeve irrigation, 21G (Ø0.80mm), asp. port Ø0.30mm
SL 116 s1	I/A Tip, straight, for silicone sleeve irrigation, 22G (Ø0.70mm), asp. port Ø0.30mm



I/A Tips angled 30° for silicone sleeve irrigation (silicone sleeve needed, dual-side irrigation)

Art. No.	Description
SL 119 a14	I/A Tip, angled 30°, for silicone sleeve irrigation, 19G (Ø1.00mm), asp. port Ø0.30mm
SL 119 a13	I/A Tip, angled 30°, for silicone sleeve irrigation, 20G (Ø0.90mm), asp. port Ø0.30mm
SL 119 a12	I/A Tip, angled 30°, for silicone sleeve irrigation, 21G (Ø0.80mm), asp. port Ø0.30mm
SL 119 a11	I/A Tip, angled 30°, for silicone sleeve irrigation, 22G (Ø0.70mm), asp. port Ø0.30mm



I/A Tips angled 45° for silicone sleeve irrigation (silicone sleeve needed, dual-side irrigation)

Art. No.	Description
SL 119	I/A Tip, angled 45°, for silicone sleeve irrigation, 19G (Ø1.00mm), asp. port Ø0.35mm
SL 119 a24	I/A Tip, angled 45°, for silicone sleeve irrigation, 19G (Ø1.00mm), asp. port Ø0.30mm
SL 119 a23	I/A Tip, angled 45°, for silicone sleeve irrigation, 20G (Ø0.90mm), asp. port Ø0.30mm
SL 119 a22	I/A Tip, angled 45°, for silicone sleeve irrigation, 21G (Ø0.80mm), asp. port Ø0.30mm
SL 119 a21	I/A Tip, angled 45°, for silicone sleeve irrigation, 22G (Ø0.70mm), asp. port Ø0.30mm



I/A Tips curved for silicone sleeve irrigation (silicone sleeve needed, dual-side irrigation)

Art. No.	Description
SL 118 c4	I/A Tip, curved, for silicone sleeve irrigation, 19G (Ø1.00mm), asp. port Ø0.30mm
SL 118 c3	I/A Tip, curved, for silicone sleeve irrigation, 20G (Ø0.90mm), asp. port Ø0.30mm
SL 118 c2	I/A Tip, curved, for silicone sleeve irrigation, 21G (Ø0.80mm), asp. port Ø0.30mm
SL 118 c1	I/A Tip, curved, for silicone sleeve irrigation, 22G (Ø0.70mm), asp. port Ø0.30mm



Please note: The expected lifetime of our reusable medical devices is validated by a defined number of processing cycles. Please refer to the information provided in the instructions for use.

02/2026